# AN/AVS-9 SERIES (F4949) **AVIATION NIGHT VISION GOGGLE**



## **KEY BENEFITS**

- Gen 3 gated Pinnacle® tubes provide the highest performance available under all light levels encountered during night flying operations
- Improved objective lens focus maximizes image clarity at all times
- Optional clip-on power source allows ANVIS usage without helmet
- Independent eye-span adjustment (IPD) and 25-mm eye relief eyepiece accommodate eyeglasses
- Low-profile battery pack improves head mobility for aviator while in cockpit and offers increase battery life
- Class A, B, C, D, and UK 645 minus-blue filters for objective lens available to suit all types of cockpit lighting, including color displays and fighter HUDs
- Manufactured in compliance with the Naval Surface Warfare Center, Crane Division specification PS/10/JXQ10/2918

For more than 60 years, Elbit Systems of America - Night Vision has provided the military with premier vision-enhancing solutions. First developed in 1992, our AN/AVS-9 series (F4949) night vision system is the standard night flying system for the air crews of the U.S. Air Force and Navy and is in service with militaries worldwide. The AN/AVS-9 is manufactured in compliance with the Naval Surface Warfare Center, Crane Division specification PS/10/JXQ10/2918. All systems are qualified according to that specification and tested to meet customer requirements. Rotary-wing versions of the AN/AVS-9 feature a rear-mounted, low-profile battery pack, which uses four AA batteries, allowing operation for more than 50 hrs. Power is provided by a cable extending from the battery pack, over the helmet, and into a connector in the mount. Our AN/AVS-9 series of aviator's night vision systems is available in over 40 different configurations. The type of aircraft and type of helmet being used will determine the configuration that is appropriate for each particular user. The lightweight binocular can be mounted to a variety of aviator helmets, including the SPH-4B, the HGU-56/P, and various ALPHA configurations.



# AN/AVS-9 SERIES (F4949) AVIATION NIGHT VISION GOGGLE

SYSTEM SPECIFICATIONS

#### STANDARD ACCESSORIES

- Carrying case
- Lens caps
- Demist shields, sacrificial lenses
- Operator kit (manual, quick reference card, lens paper)
- Low profile battery pack

## OPTIONAL ACCESSORIES (FOR EXAMPLE)

- Shipping and storage case
- Helmet mount
- Clip-on power source

OPTICAL SPECIFICATIONS	
• Field of View	• 40° nominal
Magnification	• 1X
PHYSICAL SPECIFICATIONS	
Weight (binocular only)	• 550 g maximum
Dimensions	• 3.3 x 5.1 x 4.1 in (8.3 x 13 x 10.3 cm)
Automatic Breakaway	• 11 - 15 g
ELECTRICAL SPECIFICATIONS	
• Battery Life	Nominally 30 hours (per side) under standard conditions
• Battery Type	• Fixed wing: 2 ea. 1/2 AA size, lithium, Rotary wing: 4 ea. AA size, alkaline
Operating Temperature Range	• -25.6°F to 125°F (-32°C to +52°C)
MECHANICAL SPECIFICATIONS	
Diopter Adjustment	• +2 to -6 diopters
Interpupillary Adjustment	Independent, 52 to 72 mm total
Fore-and-Aft Adjustment	• 27 mm, range
• Tilt Adjustment	• 10°, range
Exit Pupil/Eye Relief	• On-axis: 14 mm @ 25 mm distance, Full-field: 6 mm @ 25 mm distance

This datasheet applies to several variations and/or model numbers of the AN/AVS-9 series (F4949) aviation night vision goggle. Differences can be related to component variations or the image intensifier specification. All questions should be referred to nightvision@elbitsystems-us.com.

MDS-F4949